

B2782A - 63" Two stage snowblower

For:

B series tractors, L3400, L3130, L3430



FEATURES:

Dedicated 63" front mount snowblower

The B2783A chute and reduction package is now included and factory assembled eliminating the BL2583 rear 3pt hitch. This kit is NOT set up for a rear mount snowblower option.

Large greasable pillow block bearings for auger.

Chute base raised 1" above snowblower housing. (This prevents sitting water from freezing around chute and rendering rotation inoperable) Industrial type wrap-around chute base retaining plates

Manual chute rotation open spiral gear set at an angle (This aligns the gear with the crank handle reducing universal joint operating angle which reduces binding in the mechanism)

Optional hydraulic chute rotation. Optional electric chute deflector

| SPECIFICATIONS | | |
|--|----------|--|
| Overall length | in (mm) | 149.7 (3802) w/ 3-pt hitch |
| Overall width | in (mm) | 63.0 (1600) |
| Overall height | in (mm) | Auger housing: 22.75 (578) - Maximum Discharge Chute: 47.0 (1194) - Minimum |
| Cutting width | in (mm) | 63.0 (1600) |
| Cutting height | in (mm) | 21.25 (540) |
| Reach from centerline of front axle to scraper blade | in (mm) | 54.9 (1394) |
| Reach from centerline of front axle to auger shaft | in (mm) | 47.6 (1209) |
| Impeller diameter | in (mm) | 17.5 (445) |
| Impeller housing width | in (mm) | 18.0 (457) |
| Impeller width | in (mm) | 6.5 (165) |
| Auger diameter | in (mm) | 14.0 (356) |
| Auger height | in (mm) | 16.0 (406) |
| Auger clearance from ground | in (mm) | 2.0 (51) |
| Flighting pitch | in (mm) | 16.0 (406) |
| Lift height above ground level | in (mm) | Operating position: 7.25 (184) Transport position: 10.5 (267) |
| Cutting depth below ground level | in (mm) | 6.75 (171) |
| Maximum angle of approach | deg. | Operating position: 10 degrees Transport position: 15 degrees |
| Number of impellers | | 1 |
| Impeller speed @ PTO rpm | | 764 rpm @ 2500 PTO rpm |
| Auger speed @ PTO rpm | | 153 rpm @ 2500 PTO rpm |
| Chute rotation | deg. | 220 |
| Discharge chute diameter | in (mm) | 7.75 (197) |
| Capacity ton/hour (estimated) | | 250 |
| Hydraulic system (tractor or external) | | Tractor |
| Package weight | lbs (kg) | 320 (145) |