

**T2724 SNOWBLOWER SPECIFICATIONS**  
**FOR T1460, T1560 AND T1760 TRACTORS**  
**AND T1880, T2080 AND T2380 NEWS TRACTORS**

Type	Clockwise
Overall width	46"
Overall height without chute	19"
Overall height with chute	44"
Overall length without subframe	21"
Overall length with subframe	69 1/2"
Overall length with tractor	99 1/2"
Overall length with tractor and rear weight bracket	105 5/8"
Cutting width	46"
Cutting height	17 1/2"
Frame thickness	16 Ga.
Side thickness	12 Ga.
Thickness of impeller back housing	14 Ga.
Thickness of impeller side housing	16 Ga.
Number of phases	2
Drive	Belt type B
Auger drive	Worm gear box ratio 5:1
Auger RPM (T1560 tractor)	232 RPM
Auger RPM (T1880 tractor)	232 RPM
Auger diameter	12 3/4"
Auger pitch	15"
Impeller RPM (T1560 tractor)	1156 RPM
Impeller RPM (T1880 tractor)	1159 RPM
Impeller diameter	13 3/4"
Impeller width	5"
Number of blades on impeller	3
Chute position	Left
Chute rotation	Manual
Adjustable deflector	Yes
Adjustable skid shoes	Yes
Replaceable cutting edge	Yes
Number of shear bolts on auger	2
Number of shear bolts on impeller	1
Lift arm tension (when snowblower is on ground level)	28 lbs
Snowblower lifting height with T1760 tractor (option A)	5 1/8"
Snowblower lifting height with T1760 tractor (option B)	4 1/2"
Snowblower lifting height with T1460 and T1560 tractor (option A)	4 5/8"
Snowblower lifting height with T1460 and T1560 tractor (option B)	4"
Snowblower lifting height with T1880 tractor (option A)	3 3/8"
Snowblower lifting height with T1880 tractor (option B)	2 3/4"
Minimal angle of approach of snowblower (on T1880 tractor, Option B)	5°
Approx. weight non-crated	212 lbs
Approx. shipping weight (crated)	325 lbs
Overall width of crate	51 1/4"
Overall length of crate	39"
Overall height of crate	26 1/2"

Note: Use this snowblower with 5 weights of 25 lbs.  
Chains on rear wheels are recommended.