

Bush Hog® TOUGH Tri-Deck Flex Finishing Mowers

BUSH HOG® TOUGH FEATURES

- TOUGH Fabricated 7 Gauge Decks
- TOUGH Commercial Grade Spindles
- TOUGH 5 Year Gearbox Limited Warranty
- TOUGH Kevlar Reinforced Belts
- TOUGH 4x4 Inch Boxed Wing Section Lift Arms
- TOUGH Powder Coat Paint



Model 1500



Model 1100

MODELS	TD-1100	TD-1500	TD-1700
Cutting Width	11 ft	15 ft	17 ft
Cutting Height	3/4 to 41/4 inches	11/2 to 41/2 inches	11/2 to 41/2 inches
Transport Width	6 ft 6 inches	8 ft	8 ft
Transport Height	6 ft 3 inches	8 ft	9 ft
Transport Length	12 ft	14 ft	14 ft
Minimum Tractor HP*	30 PTO	40 PTO	40 PTO
Type Hitch	Pull Type, Clevis Hitch, Three-Position Adjustment		
Gearbox	45 HP center wings/80 HP transfer box for all 3 models		
Tractor PTO Speed	540 RPM	540 RPM	540 RPM
Driveline Size	Category 4 80° CV (Main) - Category 3 (Decks)		
Wing Section Lift Arms	4 x 4 inch Boxed Section	4 x 4 inch Boxed Section	4 x 4 inch Boxed Section
Wing Flex	30° Up & 10° Down	30° Up & 10° Down	30° Up & 10° Down
Wing Deck Flex	10° Side to Side, 10° Front to Rear - Independent of the Wing Frame		
Tire Size	23 x 9.5 (2)	23 x 8.5 (2)	23 x 8.5 (2)
Deck Widths	(3) 4 ft	(1) 6 ft and (2) 5 ft	(3) 6 ft
Deck Plate	7 gauge	7 gauge	7 gauge
Blade Tip Speed	18,468 FPM	18,271 FPM (18,231 Wings)	18,271 FPM
Gauge Wheels	10 x 4 inches	13 x 5 inches	13 x 5 inches
Belt	(1) per Deck "B" size Kevlar	(1) per Deck "B" size Kevlar	(1) per Deck "B" size Kevlar
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler	Spring Loaded Idler
Deck Overlap	6 inches	6 inches	6 inches
Blade Overlap	11/2 inches	11/2 inches	11/2 inches
Front Roller Size (Standard)	3 x 5 inches	3 x 5 inches	3 x 5 inches
Approximate Weight	2450 lbs	2752 lbs	2855 lbs
Options (TD-1100 only)	Underside roller kit for each deck, double acting hydraulic cylinder conversion kit		
Warranty	1 year limited warranty with a 5 year gearbox limited warranty		

FEATURES

- Rear discharge
- High blade tip speeds

*Minimum horsepower will be subject to change due to mowing conditions

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE